


MIL-C-55302 / 55

UMR-FF Series


Female Body / Female Contact: .100" Centers — .050" offset

ORDERING INFORMATION

MIL-C-55302 / 55




AVAILABLE CONTACTS



UMR / UER -
FEMALE CONTACTS

Contact Style	Terminal Type	Contact Term		Extension G ± .010
		CCC	MIL-C	
Female	Solder Cup	0	A	.100 (2.54)
	Dip Solder	2	B	.140 (3.56)
	Dip Solder	3	C	.172 (4.37)
	Dip Solder	4	E	.234 (5.94)
	Flexible Circuit	5	D	.058 (1.47)
	Flexible Circuit	6	F	.100 (2.54)



Designation UMR

RYTON
POLYPHENYLENE
SULFIDE
MIL-M-24519
TYPE GST-40F
COLOR BLACK
STANDARD

026

NUMBER OF
CONTACTS:
10-70

FF

BODY / CON-
TACT STYLE
DESIGNATION:
FF = FEMALE
SOCKET
CONTACT,
CLOSED ENTRY

2

CONTACT
TERMINATION:
0, 2, 3
4, 5, 6

KS

TYPE (S) OF
MOUNTING
HARDWARE.
OTHER TYPES
SHOWN ON
PG. 24