
Continental Connectors Part Number Ordering Information



UMR, UER, URR, UWR

Connector Body (insulator) material:

Polyphenylene Sulfide, Type GST-40F, per MIL-M-24519

UER available in 90, 100 and 120 with male body



Number of contacts:

10, 14, 20, 24, 26, 30, 36, 40, 44, 50, 56, 60, 66, 70

Note: URR and UWR

series also available in 90, 100, and 120 contacts.



Contact Termination: 0 = Standard

- Solder Cup = Dip Solder ---
- .110 Long
- 2 = Dip Solder ---.140 Long
- 3 = Dip Solder .172 Long 4 = Dip Solder
- .234 Long 5 = Flexible Circuit ---.058 Long
- 6 = Flexible Circuit --.100 Long



Deviation Code:

Consult Factory

Polarizing Hardware Position:

Required Only With Y & YF "D" Shape Guides (See Chart For Polarizing Position Desired)

Optional -

Body & Contact Style Designation:

- = Female body & Beryllium copper female socket contact, closed entry standard
- = Female body & low insertion force, female socket contact closed entry, Beryllium copper
- = Female body & half hard brass male pin contact - standard
- = Male body & phosphor bronze male pin contact — standard
- = Male body & Beryllium copper female socket contact, closed entry — standard
- MFL = Male body & low insertion force, female socket contact, closed entry, Beryllium copper - standard

Hardware Variations:

- X = Round Guide Extended Mounting Threaded
- XF = Round Guide --Flush Mounting
- "D" Shape Guide Extended Mounting Threaded
- YF = "D" Shape Guide ---Flush Mounting
- KS = Turnable Screwlock --.200 Large Knob
- KM= Turnable Screwlock --.500 Large Knob
- KL = Turnable Screwlock .700 Large Knob
- KH = Turnable Screwlock -Hex. Socket Drive
- SL = Fixed Screwlock --Extended Mounting Threaded
- SF = Fixed Screwlock Flush Mounting

