

10

9

8

7

6

5




4

3

2

SD-8361 X1 31 7

PART REV	DWG ISSUE	DATE	ECN NO.	APPVD BY	REL BY



PART NUMBER	SIZE	A MAX	B	C
836111317	9	.785 [19.94]	.565 [14.35]	.133 [3.38]
836121317	15	.935 [23.75]	.715 [18.16]	.170 [4.32]
836131317	21	1.085 [27.56]	.865 [21.97]	.170 [4.32]
836141317	25	1.185 [30.10]	.965 [24.51]	.183 [4.65]
836151317	31	1.335 [33.91]	1.115 [28.32]	.183 [4.65]
836161317	37	1.485 [37.27]	1.265 [32.13]	.183 [4.65]

- 5 CONSULT FACTORY FOR AVAILABLE OPTIONS
4. PERFORMANCE: MEETS OR EXCEEDS THE REQUIREMENTS OF MIL-DTL-83513
3. SEE SHEET 2 FOR RECOMMENDED PCB LAYOUTS

- 2 MATERIALS:
SHELL: 6061-T6 ALUMINUM PER AMS-QQ-A200/8, NICKEL
PLATED PER AMS 2404
INSULATOR AND BACKSHELL: PPS PER MIL-M-24519 GST-40F, COLOR: BLACK
PIN CONTACTS: C17200 BERYLLIUM COPPER PER ASTM B194,
GOLD PLATED PER ASTM B488
24 AWG LEADS: TIN PLATED COPPER ALLOY PER A-A-59551 TYPE S
JACKPOSTS: PASSIVATED STAINLESS STEEL IAW MIL-DTL-83513/5

1. MARKING: "UMI", DATE CODE, AND UMI PART NUMBER

NOTES: UNLESS OTHERWISE SPECIFIED

QUALITY SYMBOLS	UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES/MM	SCALE NONE	DWG SIZE B	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
MAJOR ▲	GENERAL TOLERANCES: 3 PLACE ±.002/.051 2 PLACE ±.005/.13 ANGULAR ±2°	DRAWN BY & DATE DW 2-6-12	TITLE: CIRCUIT CONNECTOR, PLUG, STYLE 9 (.075 X .075), SIZES 9 THRU 37, CM9RXXP07-S01	APPROVED BY & DATE	MATERIAL: 2 5 Uti-Mate Connector Inc.
CRITICAL ▼	Uti-Mate CAGE CODE 58967	CAD FILENAME SD-8361 X1 31 7-1.DGN	PART NO. SEE CHART	DRAWING NO. SD-8361 X1 31 7	SHEET NO. 1 OF 2
SPC S		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ULTI-MATE INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			REV

10

9

8

7

6

5







4

3

2

SD-8361X1317

PART REV	DWG ISSUE	DATE	ECN NO.	APPVD BY	REL BY



QUALITY SYMBOLS	UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES/MM	SCALE 4:1	DWG SIZE B	 THIRD ANGLE PROJECTION	REVISE ON CAD ONLY		
	GENERAL TOLERANCES: 3 PLACE ± .002/.051 2 PLACE ± .005/.13 ANGULAR ±2°	DRAWN BY & DATE DW 2-6-12					TITLE: RECOMMENDED PCB LAYOUTS, STYLE 9 PLUG (.075 X .075), SIZES 9 THRU 37, CM9RXXP07-S01
		CHECKED BY & DATE					
		APPROVED BY & DATE					
MAJOR =				MATERIAL: SEE SHEET 1	Ulti-Mate Connector Inc.		
CRITICAL C =		CAD FILENAME SD-8361X1317-2.DGN	PART NO. SEE SHEET 1	DRAWING NO. SD-8361X1317	SHEET NO. 2 OF 2		
SPC S =	Ulti-Mate CAGE CODE 58967	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ULTI-MATE INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.				REV	

Ulti-Mate
Connector Inc.